

Christie Boxer 2K20, 2K25 and 2K30

		Christie Boxer 2K20 144-007108-01	Christie Boxer 2K25 144-008109-01	Christie Boxer 2K30 144-009100-01
Image	brightness	• 19,500 ANSI (typical) • 20,000 Center • 22,000 ISO	• 24,500 ANSI (typical) • 25,000 Center • 27,500 ISO	• 29,000 ANSI (typical) • 30,000 Center • 32,500 ISO
	contrast	• 2000:1		
Display technology	type	• 3DLP® 1.38" DMD		
	resolution	• 2K (2048 x 1080)		
Lamp	type	• 4 x 450W NSH	• 5 x 450W NSH	• 6 x 450W NSH
	life	• 1500 hrs to 70% initial brightness		
Inputs		• HB multi input card • HDBaseT		
Pixel clock		• 300 Mpx/s - Christie® TruLife Lite Electronics		
Networking		• Keypad • RS232 in • Ethernet (10/100) RJ45		
Lens mount		• Tool-free lens insertion system • Boresight adjustable • Motorized horizontal and vertical lens offset • Motorized zoom and focus adjustment		
Lenses	fixed	• 0.72:1 (no offset) • 0.9:1 (offset: V: ±45%, H: ±15%)		
	zoom	• 1.13-1.31:1 (offset: V: ±60%, H: 25%) • 1.31-1.63:1 (offset: V: ±80%, H: 30%) • 1.63-2.17:1 (offset: V: ±80%, H: 30%) • 1.99-2.71:1 (offset: V: ±15%, H: 5%) • 2.71-3.89:1 (offset: V: ±45%, H: 15%) • 3.89-5.43:1 (offset: V: ±85%, H: 25%) • 4.96:1-7.69:1 (offset: V: ±55%, H: 20%)		
Optional accessories		• Dual link DVI input card • Twin HDMI™ input card • Dual 3G HD-SDI input card • Twin DisplayPort input card • Rigging and stacking frame • HB multi input card • Quad DisplayPort input card (HB)		
Power requirements	operating voltage	• 200-240V		
	operating current	• 19A		
Dimensions	size	• (LxWxH): 37.75 x 23.5 x 12" (959 x 597 x 305mm)		
	weight	• 160lbs (72.57kg)		
Operating environment	temperature	• 41-104°F (5 to 40°C)		
	humidity	• 10-80%, non-condensing		
Warranty		• Three years		

For Christie Boxer 4K30 specs, please visit christiedigital.com.

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610
Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888
Brazil
ph: +55 (11) 2548 4753
China (Beijing)
ph: +86 10 6561 0240
China (Shanghai)
ph: +86 21 6278 7708
France
ph: +33 (0) 1 41 21 44 04

Germany
ph: +49 2161 664540
India
ph: +91 (080) 6708 9999
Japan (Tokyo)
ph: 81 3 3599 7481
Korea (Seoul)
ph: +82 2 702 1601
Mexico
ph: +52 55-4744-1790

Republic of South Africa
ph: +27 (0) 11 510 0094
Russian Federation
and Eastern Europe
ph: +36 (0) 1 47 48 100
Singapore
ph: +65 6877 8737
Spain
ph: +34 91 633 9990
United Arab Emirates
ph: +971 4 3206688

United Kingdom
ph: +44 (0) 118 977 8000
United States (Arizona)
ph: 602 943 5700
United States (New York)
ph: 646 779 2014
**Independent sales
consultant offices**
Italy
ph: +39 (0) 2 9902 1161



For the most current specification information, please visit www.christiedigital.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4208 Jan 16

CHRISTIE®